# Legacy Harness

# **NEW BANDOLIER HARNESS**

#### Features:

- Features elastic loops for adjustment of the strap intersection
- Extended upper straps go over the shoulder
- Quick release buckles located near the chair back
- Stand behind user and pull finger loops to adjust top straps
- Hardware to attach to chair included



Description	Part Number	Padded Area Dimensions
Small	30639	1.5" x 14"
Medium	30640	1.5″ x 16″
Large	30641	1.5" x 18"

Bandolier Harness	Top Strap sections adjustment w/hardware	Bottom Strap adjustment w/hardware
Small	13" maximum	15" maximum
Medium	13" maximum	15" maximum
Large	13" maximum	15" maximum

STRETCH

BAND	OLIER HARNESS

## PADDED X-STYLE HARNESS

#### Features:

- Cushioned harness with reinforced webbing
- X-Style harness has minimal stretch
- Extended upper straps go over the shoulder
- Quick release buckles located near the chair back
- Stand behind user and pull finger loops to adjust top straps
- Hardware to attach to chair included



Description	Part Number	Padded Area Dimensions
Small	30519	1.5″ x 10″
Medium	30520	2" x 13"
Large	30521	2.5″ x 16″


X-Harness	Top Straps	Finger Loop Straps, without hardware	Bottom Straps, without hardware
Small	8″ long	10" long	23" long
Medium	10″ long	16" long	23" long
Large	12″ long	18″ long	23" long



# HARNESS

### PARTS DESCRIPTION

- All parts shown here are not included with every harness
- $\bullet$  Parts included vary depending on which harness you have



This harness is a **Kit** that you assemble as needed for your particular application. This sheet illustrates **examples** of the many ways to use the various straps, clips, and buckles.


#### HOW TO ATTACH A QUICK RELEASE BUCKLE TO A STRAP

• Pull Strap for desired tight fit.



When threading a Strap, the Buckle piece must have the correct side up. The part the Strap goes around has a flat side that belongs on top, and a triangular side that belongs on the bottom.





Thread the Strap as shown. If the Strap has a Finger Loop, the Finger Loop should be on the top.





# HOW TO ATTACH A STRAP TO THE CHAIR

 Secure Cam Lock Buckle and/or Metal Attaching Clip to chair, then depending on the width of the strap, thread strap as shown.

Cam Lock Buckle


Metal Attaching Clip & 1" Strap







Metal Attaching Clip & 1.5" Strap

Metal Attaching Clip & 2" Strap





• Thread the strap through a **3-Bar Slide** as shown, looping strap around the wheelchair tube, and pull tight to hold harness in desired position.



## **REMOVING USER FROM CHAIR**

 Use Quick Release Buckles so you don't have to refit all the adjustments the next time user gets into chair.

### **IMPORTANT NOTICE**

 THIS IS NOT A SAFETY DEVICE. IT IS TO BE USED ONLY FOR POSITIONING. IT MUST BE USED IN CONJUNCTION WITH A METAL SEAT BELT!

08747

9450 W Laraway Rd Frankfort, IL 60423 www.Therafin.com 800-843-7234 Fax 888-479-1515 info@Therafin.com